Certified Quality and Environmental Management Systems

Blendex S12 20

Description

BLENDEX S12 20 is a thermoplastic polyurethane in methyl-ethyl-ketone solution, with a transparent yellowish appearance. Dry density of 1,2 g/cm³.

Application

BLENDEX S12 20 is used as soft heat sealable adhesive for lamination of various products, like PU, PVC, TR, leather, synthetic leather and fabrics.

Technical Specifications

Method of analysis	MU	Standard
1. **Total Solids**	%	20±1 [1]
3. **Brookfield Viscosity 25°C**	cps	2,000 - 6,000 [2]
95. **Heat Sealability**	°C	> 70
-. **Solvents**		MEK

[1] (S 12/20)
[2] No 4 RV; 20 RPM

Handling

Reactivation temperature: over 70°C.
After reactivation, the product has good adhesive properties for a quite long time (open time).

Packing

BLENDEX S12 20 is supplied in 200-50-25 l drums

Storing

Product must be stored at temperature not higher than 30°C.
Shelf life is 6 months.

Build date 23 Oct 2009

Above information is reliable, but does not constitute warranty.

ICHEMCO srl
via 11 Settembre, 5 - 20012 CUGGIONO (MI) - ITALY
Phone: +39 02 97243.1 - Fax: +39 02 97243.200 - email: info@ichemco.it - internet: www.ichemco.it