

## Release PP 25 ECO

OBSOLETE

### Description

Release PP 25 ECO is a polyvinylcarbamate release agent in aliphatic solvent solution.

### Application

Product is designed to be used as a very efficient release agent, during production of adhesive tapes based on following films: polypropilene, polyethylene, PVC, reinforced PVC, polyester; with natural, synthetic rubber and acrylic adhesives. It also designed to be used with the three steps printing process of PSA tapes, when aromatic solvents aren't accepted.

### Technical Specifications

Method of analysis	MU	Standard
1. <b>Total Solids</b>	%	23±1
5. <b>Melting Range</b>	°C	60 - 80

### Notes

Release PP 25 ECO has the tendency to gelation when stored at temperatures below +18°C.

Properties can be restored completely by heating it up to 30-35°C and stirring the solution until perfectly clear. Diluted solutions don't suffer low temperatures (5-10°C).

### Handling

1 part of RELEASE PP 25 ECO must be added with 20/30 parts of a aliphatic solvent solution: octane-isopropylic alcohol: 80-20, if it will be applied on corona treated films. It must be diluted at lower concentrations (0,3-0,4%), when it has to be applied on untreated films.

### Packing

Product is packed in 50 kg metal drums.

### Storing

Shelf life is 6 months.