

Tacksol 10/83 B

Description

TACKSOL 10/83B is a solvent pressure sensitive adhesive, based on natural rubber and special resins, with very good performances. It has got very good resistance to ageing and heat.

Application

TACKSOL 10/83B can be applied on any substrate (paper, polyester, PP, PE, PVC, ...). It is particularly suitable for the production of protective p.s. films and tapes.

Packing

TACKSOL 10/83B is supplied in 200 litres (about 140 kg net) iron drums.

Storing

Shelf life is 6 months.

Technical Specifications

Method of analysis	MU	Standard
1. Total Solids	%	22±1
3. Brookfield Viscosity 25°C	cps	4,000 - 10,000 ⁽¹⁾
- Solvents		hexane

⁽¹⁾ No 4 RV; 20 RPM

Film properties

Method of analysis	MU	Standard
11. Peel Adhesion on Steel	g/in	700
17. Rolling Ball Tack	cm	2
22. Holding Power of Pressure Sensitive Tapes	h	> 100

Average values; 22±2 g/m² of dry adhesive on PES film 23 µm

Handling

When heat or mechanical resistance must be increased, 0,5 - 1% of CURING AGENT D or RF/AE should be added; taking care that the pot-life of the adhesive is reduced to 24 hours (maximum).