

## Tacksol 10/86

### Description

TACKSOL 10/86 is a solvent pressure sensitive adhesive, based on natural rubber and special resins. After curing, it develops very good resistance to ageing, light and heat.

### Application

TACKSOL 10/86 can be applied on any substrate (paper, polyester, PP, PE, PVC,...). This product is suggested for the production of protective p.s. films and tapes.

### Technical Specifications

Method of analysis	MU	Standard
1. <b>Total Solids</b>	%	20±1
3. <b>Brookfield Viscosity</b> 25°C	mPa.s	2,000 - 10,000 <sup>(1)</sup>
- <b>Solvents</b>		hexane

<sup>(1)</sup> No 4 RV; 20 RPM

### Film properties

Method of analysis	MU	Standard
11. <b>Peel Adhesion on Steel</b>	g/in	800 - 1,100
17. <b>Rolling Ball Tack</b>	cm	2 - 4
22. <b>Holding Power of</b> <b>Pressure Sensitive</b> <b>Tapes</b>	h	> 100

Average values; 22±2 g/m<sup>2</sup> of dry adhesive on PES film 23 µm

### Handling

When heat or mechanical resistance must be increased, 0,5 - 1% of CURING AGENT D should be added, remembering that pot-life of the adhesive in that case is reduced to a maximum of 24 hours.