

## Tacksol 10/86 HT

### Description

TACKSOL 10/86 HT is a solvent pressure sensitive adhesive, based on natural rubber and special resins. It has a good wettability on various substrates.

### Application

TACKSOL 10/86 HT can be applied on any substrate (paper, polyester, PP, PE, PVC). It is a soft adhesive and is suggested for the production of protective p.s. films and tapes.

### Technical Specifications

Method of analysis	MU	Standard
1. <b>Total Solids</b>	%	30±1
3. <b>Brookfield Viscosity</b> 25°C	mPa.s	2,000 - 6,000 <sup>(1)</sup>
- <b>Solvents</b>		hexane

<sup>(1)</sup> N. 5 RV; 20 RPM

### Film properties

Method of analysis	MU	Standard
11. <b>Peel Adhesion on Steel</b>	g/in	1,000 - 1,300
17. <b>Rolling Ball Tack</b>	cm	0.5 - 3
22. <b>Holding Power of</b> <b>Pressure Sensitive</b> <b>Tapes</b>	h	> 100

Average values; 22±2 g/m<sup>2</sup> of dry adhesive on PES film 23 µm

### Handling

TACKSOL 10/86 HT can be diluted with aliphatic and aromatic solvents to obtain the correct viscosity. For protective tapes it is necessary to cure the product with CURING AGENT D (0,5 - 1%), remembering that pot-life of the adhesive is reduced

to a maximum of 24 hours.

### Packing

TACKSOL 10/86 HT is supplied in 200 litres (about 140 kg net) iron drums.

### Storing

Shelf life is 6 months.