

Tacksol 10/86 HTM

Description

TACKSOL 10/86 HTM is a solvent pressure sensitive adhesive, based on natural rubber and special resins. It has a good wettability on various substrates.

An important feature of TACKSOL 10/86 HTM is its very low viscosity.

Application

TACKSOL 10/86 HTM can be applied on any substrate (polyester, PP, PE, PVC).

It is a soft adhesive, suggested for the production of protective p.s. films and tapes.

Technical Specifications

Method of analysis	MU	Standard
1. Total Solids	%	17±1
3. Brookfield Viscosity 25°C	cps	70 - 150 ⁽¹⁾
- Solvents		heptane / hexane

⁽¹⁾ No 1 RV; 20 RPM

Film properties

Method of analysis	MU	Standard
11. Peel Adhesion on Steel	g/in	600
17. Rolling Ball Tack	cm	3
22. Holding Power of Pressure Sensitive Tapes	h	> 100

Average values; 22±2 g/m² of dry adhesive on PES film 23 µm

Handling

It is necessary to cure the product with CURING AGENT RF-AE (1-1.5%), remembering that pot-life of the adhesive is reduced to a maximum of 24

hours.

Packing

TACKSOL 10/86 HTM is supplied in 200 litres (about 140 kg net) iron drums.

Storing

Shelf life is 6 months.