

Tackwhite A 41 PL

OBSOLETE

Description

TACKWHITE A 41 PL is a pure acrylic p.s.a., in water dispersion. The product has a good initial tack and a following high crystallinity.

Application

TACKWHITE A 41 PL is specially formulated for the lamination of paper and cardboard with plastic film (OPP, PE, cellulose acetate, PET, etc).

Packing

TACKWHITE A 41 PL is supplied in 200 l drums or 1000 l tanks.

Storing

TACKWHITE A 41 PL must be stored at temperature between +5°C and +40°C. Shelf life is 3 months.

Technical Specifications

Method of analysis	MU	Standard
1. Total Solids	%	53±2
3. Brookfield Viscosity 25°C	mPa.s	150 ⁽¹⁾
8. pH	pH	8 - 9
- Solvents		water

⁽¹⁾ No 1 RV; 20 RPM

Film properties

Method of analysis	MU	Standard
11. Peel Adhesion on Steel	g/in	700
22. Holding Power of Pressure Sensitive Tapes	h	> 200

Average values; 22±2 g/m² of dry adhesive on PES film 23 µm

Handling

The product can be applied using traditional coating methods: Mayer bar, rotogravure,...

If necessary, TACKWHITE A 41 PL can be thickened with acrylic products (see Ichemco catalogue, suggested product: S.L. 6103).