

Tackwhite A 62 SF

Description

TACKWHITE A 62 SF is a pure acrylic p.s.a., in water dispersion, containing rosin esters. It is a permanent adhesive, that produces a very clear and transparent film, with an excellent light stability.

Application

TACKWHITE A 62 SF is used mainly for permanent labels production (paper and plastic), double-sided tapes and foams.

Technical Specifications

Method of analysis	MU	Standard
1. Total Solids	%	50±1
8. pH	pH	7 - 9
- Solvents		water
3. Brookfield Viscosity 25°C	mPa.s	
TACKWHITE A 62 SF		150 - 500 ⁽¹⁾
TACKWHITE A 62 SF (V2)		17,000 - 27,000 ⁽²⁾

⁽¹⁾ No 1 RV; 20 RPM

⁽²⁾ No 6 RV; 20 RPM

Film properties

Method of analysis	MU	Standard
11. Peel Adhesion on Steel	g/in	800 - 1,200
17. Rolling Ball Tack	cm	2 - 4
22. Holding Power of Pressure Sensitive Tapes	h	> 2

Average values; 22±2 g/m² of dry adhesive on PES film 23 µm

Handling

The product can be applied using traditional coating systems: Meyer bar, air knife, rotogravure, ...
The coating weight depends on the final application, usually it goes from 20 to 40 g dry/sqm.

Packing

TACKWHITE A 62 SF is supplied in 200 l drums or 1000 l tanks.

Storing

TACKWHITE A 62 SF must be stored at temperature between +5°C and +40°C.
Shelf life is 3 months.