ichemco
Developing Chemical Excellence

CERTIFIED MANAGEMENT SYSTEMS
CERTIQUALITY
UNI EN ISO **9001:2015**
UNI EN ISO **14001:2015**
UNI ISO **45001:2018**

Tackwhite A 38

Description

TACKWHITE A38 is an acrylic dispersion used for wash-removable labels.

Application

Water borne pressure sensitive adhesive used for wash removable labels.
The product has a good removability in alcaline water: at 70°C clean removal in 15-30 sec.

Technical Specifications

Method of analysis	MU	Standard
1. Total Solids	%	48±1
3. Brookfield Viscosity 25°C	mPa.s	100 - 500 (1)
8. pH		8 - 9
Solvents		water

(1) No 1 RV; 20 RPM

Film properties

Method of analysis	MU	Standard
11. Peel Adhesion on Steel	g/in	1,100
17. Rolling Ball Tack	cm	10
22. Static Shear	h	> 2
97. Loop Tack Test	g	1,500

Average values; 22±2 g/m² of dry adhesive on PET film 36 µm

Handling

The product can be applied using traditional coating systems: Mayer bar, reverse gravure,...
The product can be thickened using polyurethanic or acrylic thickeners (e.g. THICKENER SL 6103).

Packaging

The product is supplied in iron drums (200 kg); IBC containers (1000 kg).

Storing

Protect from freezing.
Keep at temperatures between +5 and +35°C.

Use within 6 months from production date (unopened and in the original packaging).

Build date 11 Sep 2025

Above information is reliable, but does not constitute warranty.

ICHEMCO srl
via 11 Settembre, 5 - 20012 CUGGIONO (MI) - ITALY
Phone: +39 02 97243.1 - info@ichemco.it - www.ichemco.it