



Tackwhite A 22 RP

Description

TACKWHITE A 22 RP is a waterborne pressure sensitive adhesive, based on acrylic polymers. The coated product has a very high resistance to plasticizers and humidity. It can be classified as a permanent adhesive.

Application

TACKWHITE A 22 RP is designed for the production of labels in plastic film (especially PPVC).

Technical Specifications

Method of analysis	MU	Standard
1. Total Solids	%	51±1
3. Brookfield Viscosity 25°C	mPa.s	10 - 250 ⁽¹⁾
8. pH Solvents		5 - 6.5 water

⁽¹⁾ No 1 RV; 20 RPM

Film properties

Method of analysis	MU	Standard
11. Peel Adhesion on Steel	g/in	1,300
17. Rolling Ball Tack	cm	10
22. Static Shear	h	> 100
97. Loop Tack Test	g	1,200

Average values; 22±2 g/m² of dry adhesive on PET film 36 µm

Handling

The product can be applied by Mayer bar or reverse roll.

If necessary, it can be thickened with a suitable acrylic based thickener.

Packaging

The product is supplied in iron drums (200 kg); IBC containers (1000 kg).

Storing

TACKWHITE A 22 RP must be stored at temperature between +5°C and +40°C. Protect from freeze.

Use within 6 months from production date (unopened and in the original packaging).