



COLOR INK PVC

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier: COLOR INK PVC

UFI: 2R70-G0US-500C-63K0

1.2. Relevant identified uses of Water based printing ink.

the substance or mixture and Industrial use

uses advised against: ERC: 11a, 2, 5, 8c

PROC: 19, 2, 3, 5, 8a,

8b, 9 PC: 18

1.3. Details of the supplier of the Ichemco srl

safety data sheet: via 11 Settembre, 5

20012 Cuggiono (MI)

Italy

Email address of the competent safety@ichemco.it

person:

1.4. Emergency telephone 24hrs, UK: 844 892 0111; EU: +32 3 575 55 55

number:

Further information obtainable Product safety department

from

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification in accordance with Regulation (EC) No. 1272/2008 (CLP)

Highly flammable liquid and vapour. Flam. Liq. 2;H225

Eye Irrit. 2;H319 Causes serious eye irritation.

STOT SE 3;H336 May cause drowsiness or dizziness.

2.2. Label elements

Hazard pictograms:





GHS02

GHS07

Signal word: Danger

EUH066 Repeated exposure may cause skin dryness or cracking. Hazard statements:

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

ICHEMCO srl

via 11 Settembre, 5 20012 Cuggiono (MI) - ITALY

Phone +39 02 97243.1 - Fax +39 02 97243.200: - email: info@ichemco.it - internet: www.ichemco.it

COLOR INK PVC English Revision: 14 (19 Sep 2023) Printed on: 26 Sep 2025 Page: 1/8



Precautionary statements: P210 Keep away from heat/sparks/open flames/hot surfaces. - No

smoking.

P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face

protection.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P370+P378 In case of fire: Use suitable media (see MSDS for instruction) for extinction.

Contains: Ethyl methyl ketone - 2-methoxy-1-methylethyl acetate

2.3. Other hazards: On the basis of available data, the product does not contain PBT or vPvB

substances in quantities \geq 0.1%.

The product does not contain substances having properties of interference with the

endocrine system in a concentration \geq 0.1%.

SECTION 3: Composition/information on ingredients

3.1. Substances

n. a.

3.2. Mixtures

Substances presenting a health or environmental hazard within the meaning of directives 67/548/EEC, 1999/45/EC and 1272/2008 (CLP):

CAS	EINECS	Registration n.	Denomination	Content	Classification(*)
78-93-3	201-159-0	01-2119457290-43	Ethyl methyl ketone Butanone	50 - 70%	Eye Irrit. 2; H319 Flam. Liq. 2; H225 STOT SE 3; H336 EUH066
108-65-6	203-603-9	01-2119475791-29	2-methoxy-1-methylethyl acetate	7 - 8%	Flam. Liq. 3; H226 STOT SE 3; H336

^(*) For full text of the H- and EUH-phrases, see section 16.

SECTION 4: First aid measures

4.1. Description of first aid If you feel unwell, seek medical advice. Take off immediately all contaminated

measures: clothing.

Inhalation: Move affected person to fresh air. Seek medical advise.

Eye contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. If eye irritation persists, get medical advice.

Skin contact: Wash immediately with large amounts of water. Remove contemned clothing. If

irritation persists, seek medical advice.

Ingestion: Consult physician or poison control center immediately. Do not induce vomiting if

not asked by the physician. Do not give anything orally without medical

authorization if subject is unconscious.

4.2. Most important symptoms n. a. and effects, both acute and

delaved:

4.3. Indication of any immediate n. a. medical attention and special

treatment needed:

COLOR INK PVC English Revision: 14 (19 Sep 2023) Printed on: 26 Sep 2025 Page: 2/8

SECTION 5: Firefighting measures

5.1. Extinguishing media: Foam, dry chemical powder, carbon dioxide (CO2).

Extinguishing media which must Water Fire Extinguishers.

not be used:

5.2. Special hazards arising from Vapours are heavier than air and can travel along ground to remote ignition sources. the substance or mixture:

5.3. Advice for firefighters: Independent apparatus for respiratory protection.

Recommendations: Do not use water jets. If possible, take away any dangerous containers. Do not stay

in the direction of the bottoms of containers. Cool the containers with spray water from a safe position. Fire-fighters must wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

Stop the outpouring, if possible without hazard. Circumscribe the loss and remove it by absorbing on dry sand or other inert materials. Remove any possible source of ignition. Control vapours with spray water. Do not smoke. Avoid contact. If the product has contaminated soil or waters, inform public authorities.

6.1. Personal precautions, Wear gloves, protective clothing, safety goggles, boots, and protection for the protective equipment and respiratory (breathing apparatus). Eliminate all unguarded flames and possible emergency procedures: sources of ignition. Do not smoke. Move out of danger unprotected and

unauthorized persons.

6.2. Environmental precautions: If the product has contaminated soil or waters, inform public authorities.

6.3. Methods and material for Stop the outpouring, if possible without hazard. Circumscribe the loss and remove it containment and cleaning up: by absorbing on dry sand or other inert materials.

6.4. Reference to other sections: Please also refer to Sections 8 and 13.

SECTION 7: Handling and storage

Avoid flames and radiant heating. This product must be stored, handled and used in hygienic and safe way, according to current regulations.

7.1. Precautions for safe General ventilation is required. Local ventilation is recommended. Do not breathe handling: vapour. Avoid skin and eye contact.

Advice on general occupational (a) not to eat, drink and smoke in work areas;

hygiene: (b) to wash hands after use; and

(c) to remove contaminated clothing and protective equipment before entering eating areas.

7.2. Conditions for safe storage, Store the product in fresh, ventilated areas, separated from heating sources. Floor including any incompatibilities: must not be flammable, must be impermeable and must prevent pouring to the

outside. Electric plant must comply to current regulations.

Storage class TRGS 510 (Germany): 3

7.3. Specific end use(s): Nothing special to note about specific uses.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters:

Substance:	TLW-TWA		STEL	
	ppm	mg/m³	ppm	mg/m³
Ethyl methyl ketone	200	600	300	900
2-methoxy-1-methylethyl acetate	50	275	100	550

COLOR INK PVC English Revision: 14 (19 Sep 2023) Printed on: 26 Sep 2025 Page: 3/8

2-methoxy-1-methylethyl AGW (Deu) 270 mg/m3-50 ppm (TWA/8h); 270 mg/m3-50 ppm (STEL/15min) acetate: MAK (Deu) 270 mg/m3-50 ppm (TWA/8h); 270 mg/m3-50 ppm (STEL/15min)

VLA (Esp) 275 mg/m3-50 ppm (TWA/8h); 550 mg/m3-100 ppm (STEL/15min) VLEP (Fra) 275 mg/m3-50 ppm (TWA/8h); 550 mg/m3-100 ppm (STEL/15min) WEL (Grb) 274 mg/m3-50 ppm (TWA/8h); 548 mg/m3-100 ppm (STEL/15min) OEL (EU) 275 mg/m3-50 ppm (TWA/8h); 550 mg/m3-100 ppm (STEL/15min)

Cronic systemic effects, people, oral>1,67 mg/kg; inhalation >33 mg/kg;

dermal>54,8 mg/kg

Cronic systemic effects, workers, inhalation >275 mg/m3; dermal >153,5 mg/kg

PNEC

Soft water >0,635 mg/kg; sea water >0,0635 mg/kg; soft water sediment >3,29 mg/kg; water, intermittent release >6,35 mg/kg; sea water sediment>0,329 mg/kg, STP microorganisms >100 mg/kg; terrestrial compartment > 0,29 mg/kg

Ethyl methyl ketone: TLV-ACGIH 500 mg/m3-200 ppm (TWA/8h); 885 mg/m3-300 ppm (STEL/15 min) AGW (Deu) 600 mg/m3-200 ppm (TWA/8h); 600 mg/m3-200 ppm (STEL/15min) MAK (Deu) 600 mg/m3-200 ppm (TWA/8h); 600 mg/m3-200 ppm (STEL/15min) VLA (Esp) 600 mg/m3-200 ppm (TWA/8h); 900 mg/m3-300 ppm (STEL/15min) VLEP (Fra) 600 mg/m3-200 ppm (TWA/8h); 900 mg/m3-300 ppm (STEL/15min) WEL (Grb) 600 mg/m3-200 ppm (TWA/8h); 899 mg/m3-300 ppm (STEL/15min) OEL (EU) 275 mg/m3-50 ppm (TWA/8h); 550 mg/m3-100 ppm (STEL/15min)

DNEL - Long term systemic effects

Dermal/Workers:1161 mg/kg; Inhalation/Workers:600 mg/m3; Dermal/People:412

mg/kg; Inhalation/People: 106 mg/m3;Oral/People:31 mg/kg

PNEC (EC)

Sediment (soft water):284,74 mg/kg; Sediment (sea water):284,7 mg/kg; Soft water: 55,8 mg/l; Occasional emission: 55,8 mg/l; terrestrial compartment > 22,5 mg/kg; food chian (secondary poisoning) > 1000 mg/kg

8.2. Exposure controls: Ensure good ventilation and local exhaustion of the working area, to keep vapours

concentration below the limits.

Appropriate engineering controls: Electric plant must comply to current regulations about use of flammable products.

Eye / face protection: Glasses with side protection ("cage" glasses) (EN166).

Eye washing bottle with fresh water

Hand protection: Wear suitable gloves during handling.

Skin protection: Use full protective clothing for chemicals (working-dress, apron).

Protective shoes.

Respiratory protection: If the product is sprayed or if there is a high vapour concentration, use masks with

filter for organic vapours (brown A series).

Thermal hazards: n. a.

Environmental exposure controls: n. a.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties:

(a) Appearance: Coloured liquid.

COLOR INK PVC English Page: 4/8 Revision: 14 (19 Sep 2023) Printed on: 26 Sep 2025

```
(a) Physical state: Liquid.
                     (b) Colour: n. a.
                     (c) Odour: As solvent.
           (c) Odour threshold: n.a.
              (d) Melting point: n.a.
                Freezing point: n.a.
(e) Boiling point or initial boiling > 35 °C
        point and boiling range:
               (f) Flammability: n.a.
 (g) Lower and upper explosion n.a.
                          limit:
                (h) Flash point: -6 °C
  (i) Auto-ignition temperature: n.a.
(j) Decomposition temperature: n.a.
                         (k) pH: n.a.
         (I) Kinematic viscosity: n.a.
                 (m) Solubility: n.a.
      (n) Partition coefficient n- n.a.
      octanol/water (log value):
           (o) Vapour pressure: < 1.1 mbar (@50°C)
     (p) Density and/or relative 0.7 - 1.1 g/cm<sup>3</sup>
    (q) Relative vapour density: n.a.
     (r) Particle characteristics: n.a.
       (s) Explosive properties: n.a.
        (t) Oxidising properties: n.a.
                          COV: 63.4 % (EC Directive 2010/75/EC)
        9.2. Other information: n. a.
```

SECTION 10: Stability and reactivity

The material is stable in normal use and stocking conditions. It can release carbon oxides and vapours that can be harmful to health if taken to hot temperatures or in case of fire. It reacts exothermically with sulfuric acid. Reacts violently with light metals (aluminium) and strong oxidants.

10.1. Reactivity: n. a.

10.2. Chemical stability: The material is stable in normal use and stocking conditions.

10.3. Possibility of hazardous Keep away from oxidants, alkalis and strong acids to avoid exothermal reactions.

reactions

10.4. Conditions to avoid: Do not overheat. Avoid electrostatic charges. Avoid all sources of ignition.

10.5. Incompatible materials: Strongly oxidizing substances.

10.6. Hazardous decomposition Combustion can produce carbon oxides, toxic gases and fumes.

products:

SECTION 11: Toxicological information

11.1. Information on toxicological Product is irritant if inhaled and by eye contact. Ingestion might produce disturbs to digestive system with nausea, vomiting and stomachaches. If inhaled, congestion, irritation, cough and breathing difficulties might arise.

COLOR INK PVC English Revision: 14 (19 Sep 2023) Printed on: 26 Sep 2025 Page: 5/8

acute toxicity: Based on available data, classification criteria are not met

Ethyl methyl ketone

LC50/inhalation/rat>5000 ppm LD50/oral/rat > 2000 mg/kg LD50/dermal/rabbit> 5000 mg/kg

If swallowed, material may be aspirated into the lungs and cause chemical

pneumonitis.

2-methoxy-1-methylethyl acetate

LD50/oral/rat = 8530 mg/kg LD50/dermal/rat > 5000 mg/kg

irritation: Irritating for the eyes.

Dermatitis and dryness may occur after repeated skin contact.

Ethyl methyl ketone

Skin irritation/OECD404/test on rat: not irritating Eye irritation/OECD405/test on rabbit's eyes: irritating

2-methoxy-1-methylethyl acetate

Skin irritation test on rabbit: not irritating (OECD404)
Eye irritation test on rabbit: not irritating (OECD405)
corrosivity: Based on available data, classification criteria are not met
sensitisation: Based on available data, classification criteria are not met.

2-methoxy-1-methylethyl acetate

Skin sentitisation test on Giunea pig: not sensitising (OECD406)

repeated dose toxicity: n. a.

carcinogenicity: n. a.

mutagenicity: n. a.

toxicity for reproduction: n. a.

Information on likely routes of $\ \ n. \ a.$

exposure:

Symptoms related to the n. a. physical, chemical and toxicological characteristics:

Delayed and immediate effects n. a. as well as chronic effects from

short and long-term exposure:

Interactive effects: n. a.

11.2. Information on other The product does not contain substances having properties of interference with the hazards: endocrine system in a concentration> = 0.1%.

SECTION 12: Ecological information

Prevent contamination of soil and surface waters. Avoid dispersion of material into soil, drains or surface waters. Avoid dispersion of residues into drains.

12.1. Toxicity: Ethyl methyl ketone

EC50/Daphnia magna/48h = 308 mg/l

EC50/Scenedesmus subspicatus/96h = 2029 mg/l LC50/Pimephales promelas/96h = 2993 mg/l

2-methoxy-1-methylethyl acetate

LC100/Oncorhynchus mykiss/96 h: 180 mg/l (OECD203)

LC50/Oryzias latipes/14d: 63.5 mg/l (OECD204) LC50/Daphnia magna/48h > 500 mg/l (EU Method C2) EC50/Daphnia magna/21d > 100 mg/l (OECD211)

EC50/Pseudokirchneriella subcapitata/96h > 1000 mg/l (OECD201)

12.2. Persistence and Ethyl methyl ketone degradability: Easily biodegradable

2-methoxy-1-methylethyl acetate

Log Pow= 1,2

COLOR INK PVC English Revision: 14 (19 Sep 2023) Printed on: 26 Sep 2025 Page: 6/8

12.3. Bioaccumulative potential: Ethyl methyl ketone

Shortly bioaccumulative

Log Pow = 0.3

12.4. Mobility in soil: n. a.

12.5. Results of PBT and vPvB Based on available data, the product does not contain any PBT or vPvB substances

assessment: in quantity higher than 0.1%.

12.6. Endocrine disrupting The product does not contain substances having properties of interference with the

properties: endocrine system in a concentration> = 0.1%.

12.7. Other adverse effects: The product does not contain substances listed in Regulation 2024/590/UE

(substances that deplete the ozone layer)

SECTION 13: Disposal considerations

13.1. Waste treatment methods: Recover if possible. This material should be incinerated in authorized plants or under controlled conditions. Proceed in conformity with local and national regulation.

SECTION 14: Transport information

Transport only in accordance with ADR for road, RID for rail, IMDG for sea and ICAO for air transport.

14.1. UN number: 1210 - PRINTING INK, flammable (vapour pressure at 50 °C not more than 110 kPa)

14.2. UN proper shipping name: PRINTING INK

14.3. Transport hazard class(es): 3 - Flammable liquids

14.4. Packing group: II - Substances presenting medium danger

Classification Code (ADR 2.2): F1 - Flammable liquids having a flash-point of or below 60 °C

Mixed packing provisions MP19 - May - in quantities not exceeding 5 litres per inner packaging - be packed

(4.1.10): together in a combination packaging conforming to 6.1.4.21:

- with goods of the same class covered by other classification codes or with goods

of other classes, when mixed packing is also permitted for these; or

- with goods which are not subject to the requirements of ADR, provided they do

not react dangerously with one another.

Transport category (1.1.3.6): 2

Hazard identification No. 33 - highly flammable liquid (flash-point below 23 °C)

(5.3.2.3)

14.5. Environmental hazards: n. a.

Marine pollutant: No

14.6. Special precautions for n. a.

ıser:

14.7. Transport in bulk according to Annex II of MARPOL73/78

and the IBC Code:

IMDG Page: 3272-1 IMDG EMS: F-E S-D

IMDG MFAG: 311

Danger labels:



33 1210

COLOR INK PVC English Revision: 14 (19 Sep 2023) Printed on: 26 Sep 2025 Page: 7/8

SECTION 15: Regulatory information

Information contained in this SDS is based on the present state of our knowledge and on Regulation (EC) No 1907/2006 of the European Parliament and subsequent updates.

15.1. Safety, health and Restrictions related to the product or substances contained according to Annex XVII environmental of Regulation (EC) 1907/2006 (REACH) and subsequent amendments: 3, 40, 75 regulations/legislation specific

for the substance or mixture:

Directive 2012/18/EU: P5c

15.2. Chemical safety Not applicable assessment:

SECTION 16: Other information

This document was written by a trained technician.

Modified sections: 1,2,3,11,12,15,16

STIR ACCURATELY BEFORE USE

Full text of H phrases listed in Section 3:

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Glossary / List of acronyms

(STOT) RE - Repeated Exposure (STOT) SE - Single Exposure

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

CMR - Carcinogen, Mutagen, or Reproductive Toxicant

DNEL - Derived No Effect Level

ECHA - European Chemicals Agency

EINECS - European Inventory of Existing Commercial Substances

GHS - Globally Harmonized System

IATA - International Air Transport Association

ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG - International Maritime Dangerous Goods

Kow - octanol-water partition coefficient

PBT - Persistent, Bioaccumulative and Toxic substance

REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006

RID - Regulations concerning the International Carriage of Dangerous Goods by Rail

SDS - Safety data sheet

STOT - Specific Target Organ Toxicity

SVHC - Substances of Very High Concern

UFI - Unique Formula Identifier

vPvB - Very Persistent and Very Bioaccumulative

Users' working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified under section 1 without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this SDS is meant as a description of the safety requirements of our product: it is not to be considered as a guarantee of the products' properties.

The information in this Safety Data Sheet is provided in accordance with the requirements of the Chemicals (Hazard Information and Packaging) regulations.

COLOR INK PVC English Revision: 14 (19 Sep 2023) Printed on: 26 Sep 2025 Page: 8/8