



Hexane: limited

Alcohols: insoluble

Ethyl acetate: complete



UNI EN ISO 9001:2015 UNI EN ISO 14001:2015 UNI ISO 45001:2018

Tergum 120

(Provisional)

Description

TERGUM 120 is a stabilized pentaerythritol esterified rosin in flakes.

Application

TERGUM 120 is used as tackifier in water based, solvent and hot-melt adhesive formulations. It is widely compatible with most elastomers, waxes, paraffin-waxes and resins used in the adhesive industry. Its good oxidation resistance and well balanced composition are of special value when compounded with EVA, SBS and SIS polymers to obtain hot melts with outstanding heat stability.

Technical Specifications

Method of analysis	MU	Standard
4. Softening Point, Ring & Ball	°C	114 - 120
43. Acidity Grade 47. Colour Grade ⁽¹⁾	mg KOH/g	< 15 < 6
⁽¹⁾ 50% toluene		

Packaging

TERGUM 120 is supplied in 25 Kg paper sack.

Storing

TERGUM 120 must be stored in a dry and cool place.

Notes

SOLUBILITY: Toluene: complete

Mod. DT0104E - Tergum 120 Creation date: 23 Jul 2008 Revision: 1 Revision date: 23 Jul 2008

Above information is reliable, but does not constitute warranty.