

## Tacksol 10/88

### Description

**TACKSOL 10/88** is a solvent pressure sensitive adhesive, based on natural rubber and special resins. It has excellent wetting properties on various substrates.

### Application

**TACKSOL 10/88** can be applied on various substrates (paper, PET, PP, PE, PVC,...). This product is recommended for the production of protective p.s. films and tapes. It is a soft product, designed for low coating weight applications.

### Technical Specifications

Method of analysis	MU	Standard
1. Total Solids	%	32±1
3. Brookfield Viscosity 25°C	mPa.s	8,000 - 10,000 <sup>(1)</sup>
Solvents		heptane

<sup>(1)</sup> N. 5 RV; 20 RPM

### Film properties

Method of analysis	MU	Standard
11. Peel Adhesion on Steel	g/in	1,700
17. Rolling Ball Tack	cm	3

*Average values; 22±2 g/m<sup>2</sup> of dry adhesive on PET film 36 µm*

### Handling

**TACKSOL 10/88** can be diluted with aliphatic and/or aromatic solvents to obtain the desired viscosity. When used for protective film production, it is necessary to cure the product with CURING AGENT D (0.2-1%). In this case, the pot-life of the adhesive is reduced, as crosslinking starts immediately after the addition of the curing agent.

### Packaging

The product is supplied in iron drums (145 kg).

### Storing

Store at temperatures between +5 and + 40°C in well closed containers. Keep far from heat sources and direct sunlight.

Use within 12 months from production date (unopened and in the original packaging).