





UNI EN ISO 9001:2015 UNI EN ISO 14001:2015 UNI ISO 45001:2018

Release K 100 DI DIL. 1,5 **ECO**

Description

RELEASE K100 DI DIL. 1,5 ECO is a polyvinylcarbamate in solvent solution. It does not contain aromatic solvents.

Application

The product is a very efficient release agent for PP, PE, PVC, reinforced PVC and PET film with natural, synthetic rubber and acrylic adhesives. It is also designed to be used with the three steps printing process of PSA tapes, when aromatic solvents are not accepted.

Use within 12 months from production date (unopened and in the original packaging).

Notes

RELEASE K100 DI DIL. 1,5 ECO tends to jellify when stored at temperatures lower than +20°C: the solution becomes hazy and some material settles down to the bottom of the container. It is necessary to restore the original conditions before use, it is sufficient to heat the product at 35-40°C and stir to complete homogeneity.

Technical Specifications

Method of analysis	MU	Standard
1. Total Solids Solvents	%	2±0.10 heptane / isopropyl alcohol

Handling

Apply 3-5 g/sqm of RELEASE K100 DI DIL. 1,5 ECO as such or after dilution. Drying must be very efficient, in order to avoid any solvent residue. It can be used on corona treated as well as on untreated films.

Packaging

The product is supplied in Iron drums (18 kg).

Storing

Product must be stored at temperatures higher than +18°C, far from direct sunlight.

Mod. DT0104E - Release K 100 DI DIL. 1,5 ECO Creation date: 27 Oct 2010 Revision: 7 Revision date: 5 Dec 2018

1/1

Above information is reliable, but does not constitute warranty.