



mixer, during any phase of the adhesive

hazard for metaloxides friction.

the paste.

Packaging

preparation, either manually or pneumatically. In

In case of need of a continuous COLOR TAPE HM

extruder, you can disperse them in a mixer with

containers, you can have a continuous feeding of

The product is supplied in sacco carta 20 kg (20

solvent to 60-70% TS. By alternating the use of two

BIANCO P74 add-on into a continuous screw

the latter case, caution suggests to use inert gases (like nitrogen or carbon dioxide) to avoid explosion



Color Tape HM BIANCO P74

Description

COLOR TAPE HM BIANCO P74 is a very efficient white pigment masterbatch which is aimed at colouring adhesive masses, either solvent or hot-melt based. No solvent is involved. It is a free flowing product and is suitable for a continuous adhesive production process.

The addition of COLOR TAPE HM BIANCO P74 to the adhesive does not practically modify the adhesive properties, including its ageing, and is not cause of corrosion to the metal parts of production plants.

Aspect: dust free flakes

Type of pigments: inorganic (metal oxides)

Pigment content: 70% minimum

Other ingredients: dispersing agents, antioxidants,

thermoplastic resins as binder

Storing

Use within 12 months from production date (unopened and in the original packaging).

Application

COLOR TAPE HM BIANCO P74 is very easy to handle and avoids powder formation, storage problems and difficult packaging disposal.

Technical Specifications

Method of analysis	MU	Standard
69. Tonality		<1

Handling

In general, we suggest to use 6-8% on the dry content of the adhesive (approx 50-60% of usual pigment pastes).

When used in solvent adhesives, COLOR TAPE HM BIANCO P74 can be introduced directly into the

Mod. DT0104E - Color Tape HM BIANCO P74 Creation date: 22 May 2012

1/1

Revision date: 12 May 2014