



Storing



UNI EN ISO 9001:2015 UNI EN ISO 14001:2015 UNI ISO 45001:2018

Product must be stored at temperatures between

+5°C and +35°C. Protect from freezing.

Use within 12 months from production date (unopened and in the original packaging).

Keep the containers well closed.

Color Paste W Verde 20

(Provisional)

Description

COLOR PASTE W VERDE 20 (Green) is a water borne dispersion of organic and inorganic pigments. Total pigment concentrationis about 46 %.

Application

COLOR PASTE W VERDE 20 is a very efficient green pigment, which is aimed at colouring water borne acrylic adhesives. It is particularly suitable for the manufacture of packaging tapes.

Technical Specifications

Method of analysis	MU	Standard	
3. Brookfield Viscosity 25°C	mPa.s	500 - 1, 000 ⁽¹⁾	
58. Delta E Solvents		< 2 water	
⁽¹⁾ N. 2 RV; 20 RPM		mater	

Handling

We suggest to add 4-6 % according to the final required result. Stir it well before taking any quantity from the original drum. Filter the coloured adhesive mass before coating.

Packaging

The product is supplied in iron drums (25 kg); IBC containers (1000 kg).

Mod. DT0104E - Color Paste W Verde 20 Creation date: 3 Dec 2013 Revision: 2 Revision date: 5 May 2016

Above information is reliable, but does not constitute warranty.