





UNI EN ISO 9001:2015 UNI EN ISO 14001:2015 UNI ISO 45001:2018

Color Tape HM AVANA 81

(Provisional)

Description

COLOR TAPE HM AVANA 81 is a very efficient brown pigment masterbatch aimed at colouring adhesive masses, either solvent or hot-melt based. No solvent is involved. It is a free-flowing product and is suitable for a continuous adhesive production process.

The addition of COLOR TAPE HM AVANA 81 to the adhesive does not practically modify the adhesive properties, including ageing, and is not cause of corrosion to the metal parts of production plants.

Aspect: dust free flakes Type of pigments: inorganic (metal oxides) Pigment content: 70% minimum Other ingredients: dispersing agents, antioxidants, thermoplastic resins as binders. mixer, during any phase of the adhesive preparation, either manually or pneumatically. In the latter case, caution suggests to use inert gases (like nitrogen or carbon dioxide) to avoid explosion hazard for metaloxides friction. In case of need of a continuous COLOR TAPE HM AVANA 81 add-on into a continuous screw extruder, you can disperse them in a the mixer with solvent at 60-70% TS. By alternating the use of two vessels, you can achieve a continuous feeding of the paste.

Packaging

The product is supplied in sacco carta 20 kg (20 kg).

Storing

Use within 12 months from production date (unopened and in the original packaging).

Application

COLOR TAPE HM AVANA 81 is very easy to handle and dust free

Technical Specifications

| Method of analysis | MU | Standard |
|--------------------|----|----------|
| 58. Delta E | | < 1 |

Handling

In general, we recommend adding 6-8% based on the dry content of the adhesive (approx 50-60% of usual pigment pastes).

When used in solvent adhesives, COLOR TAPE HM AVANA 81 can be introduced directly into the

Mod. DT0104E - Color Tape HM AVANA 81 Creation date: 12 May 2014 Revision: 1 Revision date: 12 May 2014

Above information is reliable, but does not constitute warranty.