



Primer EPX-3 DRY

(Provisional)

Description

PRIMER EPX-3 DRY is a dry blend of various synthetic polymers, capable of strongly improving the adhesion of suitable inks to polypropylene films, either corona-treated or untreated.

Application

PRIMER EPX-3 DRY has been developed for printing all types of PP adhesive tapes, whatever the production system used.

Packaging

The product is packed in fibre drums, containing PE bags of 5 kg.

Storing

Store in closed containers, protected from direct sunlight. Use within 24 months from production date (unopened and in the original packaging).

Use within 24 months from production date (unopened and in the original packaging).

Technical Specifications

| Method of analysis | MU | Standard |
|--------------------|----|----------|
|--------------------|----|----------|

| | | |
|-----------------|---|------|
| 1. Total Solids | % | 99±1 |
|-----------------|---|------|

Handling

PRIMER EPX-3 DRY should be dissolved at 3% TS into a blend of cyclohexane and toluene (60:40). Solution is initially made by pre-solubilizing the product in a small amount of solvent (approx. 20% solids), by fast stirring into a suitable mixer and then diluting to the desired TS value with the remaining amount of solvent. In order to avoid aromatic solvents, a blend of cyclohexane and octane (80:20 or 90:10) can be used.

It is important to note that, being EPX-3 DRY a heterogeneous product, the content of one single bag should be completely used in one time, without splitting its content into different batches.

The use in the subsequent printing process is described in our specific brochure "Flexographic printing".