



Tackwhite A 87

OBSOLETE

Description

TACKWHITE A 87 is a water pressure sensitive adhesive, based on acrylic polymers. It produces a transparent film with very high cohesion and medium-high adhesion.

Application

TACKWHITE A 87 can be used for paper and filmic labels. The product is characterized by a good plasticizer resistance and it is suitable for application on PVC surfaces. Due to its high cohesion, the product has a good thermal resistance and there is no adhesive transfer after removal.

Technical Specifications

| Method of analysis | MU | Standard |
|---------------------------------|-------|----------------------------|
| Solvents | | water |
| 1. Total Solids | % | |
| TACKWHITE A 87 | | 55±2 |
| 3. Brookfield Viscosity 25°C | mPa.s | |
| TACKWHITE A 87 | | 500 - 1,000 ⁽¹⁾ |
| 8. pH | pH | |
| TACKWHITE A 87 | | 7 - 9 |

⁽¹⁾ N. 2 RV; 20 RPM

Handling

The suggested application is a direct Mayer bar coating system.

Packaging

Product is supplied in 1000 kg tanks and 200 kg drums.

Storing

TACKWHITE A 87 must be stored at temperature between +5°C and +40°C.
If stored in its original packaging, shelf life is 3 months.

Film properties

| | | |
|-------------------------------|------|-----|
| 11. Peel Adhesion on Steel | g/in | |
| TACKWHITE A 87 | | 800 |
| 17. Rolling Ball Tack | cm | |
| TACKWHITE A 87 | | 7 |
| 22. Static Shear | h | |
| TACKWHITE A 87 | | 100 |

Average values; 22±2 g/m² of dry adhesive on PET film 36 µm