



Tackwhite A 39 T (V2)

(Provisional)

Description

TACKWHITE A 39 T (V2) is a water borne acrylic pressure sensitive adhesive. The product dries very fast and the coated film has a very aggressive initial tack and a good adhesion.

Application

TACKWHITE A 39 T (V2) is suitable for the production of pressure sensitive packaging and office tapes on BOPP treated films. It is also suitable for other applications: label production, coating of foams, synthetic leathers and fabrics.

It is necessary to check before use the compatibility of the product with the material to be coated.

Packaging

The product is supplied in iron drums (200 kg); IBC containers (1000 kg).

Storing

For a safe storage of this emulsion, keep containers well sealed to prevent water evaporation and skin formation. The emulsion must be stored between 5°C and 40°C. Freezing must be avoided.

Use within 6 months from production date (unopened and in the original packaging).

Technical Specifications

Method of analysis	MU	Standard
1. Total Solids	%	49±1
3. Brookfield Viscosity 25°C	mPa.s	17000 - 27000 ⁽¹⁾
8. pH Solvents	pH	7 - 9 water

⁽¹⁾ No 6 RV; 20 RPM

Film properties

Method of analysis	MU	Standard
11. Peel Adhesion on Steel	g/in	600
17. Rolling Ball Tack	cm	4
22. Static Shear	h	> 200
97. Loop Tack Test	g	500

Average values; 22±2 g/m² of dry adhesive on PET film 36 µm