



Tackwhite AMC 9 B

(Provisional)

Description

TACKWHITE AMC 9 B is a removable pressure sensitive adhesive, based on acrylic microspheric polymers in water dispersion, properly modified with additives and wetting agents. The product achieves a very good wettability on any surface, combined with a very constant and clean removability.

Application

TACKWHITE AMC 9 B is suitable for the production of removable and replaceable paper labels. It is designed for direct coating onto paper substrates by conventional coating methods such as flexo or Mayer rod.

Packaging

The product is supplied in iron drums (200 kg); IBC containers (1000 kg).

Storing

TACKWHITE AMC 9 B must be stored at temperature between +5°C and +40°C, **avoiding freezing conditions.**

Keep containers closed to maintain proper pH. The product tends to separate, stir well before use.

Use within 6 months from production date (unopened and in the original packaging).

Technical Specifications

Method of analysis	MU	Standard
1. Total Solids	%	46±1
8. pH	pH	9 - 10
Solvents		water

Handling

TACKWHITE AMC 9 B may separate over time: this is typical for this type of adhesive. Stir before use: adhesive will readily redisperse under mild agitation. Check pH and adjust to values higher than 8.5 with ammonia solution, if necessary. Air operated diaphragm pumps are recommended for pumping the adhesive. Avoid the use of high speed centrifugal pumps.