



Solacril Pass 1

(Provisional)

Description

SOLACRIL PASS1 is a solvent borne acrylic pressure sensitive adhesive with a good tack.

Application

SOLACRIL PASS1, when coated on plastic films (PVC, PET, cellulose acetate), is suitable for the production of industrial pressure sensitive adhesives tapes and decals. It can be applied also on paper, PU foams, fabrics, leather and non wovens.

Technical Specifications

Method of analysis	MU	Standard
1. Total Solids	%	34±1
3. Brookfield Viscosity 25°C	mPa.s	7,000 - 12,000 ⁽¹⁾
Solvents		heptane / toluene / hexane

⁽¹⁾ N. 5 RV; 20 RPM

Film properties

Method of analysis	MU	Standard
10. Peel Adhesion on Steel	N/in	10
22. Static Shear	h	< 1
125. Loop Tack	N	12 ⁽¹⁾

⁽¹⁾ glass

Average values; 22±2 g/m² of dry adhesive on PET film 36 µm

Handling

SOLACRIL PASS1 is supplied ready for coating by rotating blade or reverse roll. Diluted, it can be applied by rotogravure or Mayer bar.

Packaging

The product is supplied in ADR compliant IBC containers (800 kg).

Storing

Store in a cool place, protected from direct sunlight and heat sources, at temperatures between +5 and +40°C. Keep material in tightly closed containers to prevent loss of solvent.

Use within 12 months from production date (unopened and in the original packaging).