





UNI EN ISO 9001:2015 UNI EN ISO 14001:2015 UNI ISO 45001:2018

Color Tape HM Avana 5 P

(Provisional)

Description

COLOR TAPE HM AVANA 5 P is a very efficient pigment masterbatch for colouring adhesive masses, either solvent or hot-melt based. No solvent is involved. It is free flowing and suitable for a continuous adhesive production process.

The addition of COLOR TAPE HM AVANA 5 P to the adhesive does not modify the adhesive properties, including ageing, and does not cause corrosion to the metal parts of production plants.

Aspect: small pellets Type of pigments: inorganic (metal oxides) Pigment content: 80% minimum Other ingredients: dispersing agents, antioxidants, thermoplastic resins as binder

Application

COLOR TAPE HM AVANA 5 P is very easy to handle, dust free, without any storage and packaging disposal problem. Being in pellets form and based on non toxic materials, products are very safe and clean in handling (see Safety Data Sheet).

Handling

In general, we racommended adding 6-8% on the dry content of the adhesive (approx 50-60% of a classical pigment paste variety). COLOR TAPE HM AVANA 5 P can be introduced directly into the mixer during any phase of the adhesive preparation. COLOR TAPE HM AVANA 5 P must be used in the same way as a solid resin.

Packaging

The product is supplied in paper bag (20 kg).

Storing

Keep the product protected from direct sunlight and humidity.

Use within 12 months from production date (unopened and in the original packaging).

Mod. DT0104E - Color Tape HM Avana 5 P Creation date: 20 Mar 2025 Revision: 1 Revision date: 20 Mar 2025

Above information is reliable, but does not constitute warranty.