



# Tackwhite A 2P 60

## OBSOLETE

### Description

TACKWHITE A 2P 60 is a water based pressure sensitive adhesive, based on acrylic polymers and rosin esters tackifiers, with good tack and excellent peel adhesion. Once dried, it produces a transparent film.

It has a high solids content and a good resistance to light, ageing, water and solvents.

Tg is about -40°C.

### Application

TACKWHITE A 2P 60 allows the production of pressure sensitive articles with good tack, good adhesion, good water and low temperatures resistance.

### Technical Specifications

Method of analysis	MU	Standard
1. Total Solids	%	55±2
8. pH	pH	6 - 8
Solvents		water
3. Brookfield Viscosity 25°C	mPa.s	
TACKWHITE A2P/60		600 - 900 <sup>(1)</sup>
TACKWHITE A2P/60 (V)		4,000 - 5,000 <sup>(2)</sup>
TACKWHITE A2P/60 (V2)		17,000 - 27,000 <sup>(3)</sup>

<sup>(1)</sup> N. 2 RV; 20 RPM

<sup>(2)</sup> No 3 RV; 20 RPM

<sup>(3)</sup> No 6 RV; 20 RPM

17. Rolling Ball Tack	cm	10
22. Static Shear	h	> 1
97. Loop Tack Test	g	1,200

Average values; 22±2 g/m<sup>2</sup> of dry adhesive on PET film 36 µm

### Handling

TACKWHITE A 2P 60 can be directly coated on PVC and plasticized PVC, PE, PP, fabrics. It can be applied by reverse roll, knife coating etc.

It can be modified with acrylic plasticizers, acrylic thickeners, plasticizers (like DOP, etc.), solvents, fillers.

### Storing

Product must be stored at temperatures between +5°C and +40°C. Protect from freeze.

### Film properties

Method of analysis	MU	Standard
11. Peel Adhesion on Steel	g/in	2,000