



# Tackwhite A 34

## OBSOLETE

### Description

TACKWHITE A 34 is a pure acrylic p.s.a., in water dispersion, containing rosin esters. It is a permanent adhesive, suitable for transparent labels, tapes and any light resistant pressure sensitive article.

### Application

TACKWHITE A 34 is used mainly for permanent labels production (paper and plastic) and foams.

### Packaging

TACKWHITE A 34 is supplied in 200 l drums or 1000 l tanks.

### Storing

TACKWHITE A 34 must be stored at temperature between +5°C and +40°C.  
Shelf life is 3 months.

## Technical Specifications

Method of analysis	MU	Standard
1. Total Solids	%	50±2
8. pH	pH	7 - 9
Solvents		water
3. Brookfield Viscosity 25°C	mPa.s	
TACKWHITE A 34		300 - 1,000 <sup>(1)</sup>
TACKWHITE A 34 (V2)		17,000 - 27,000 <sup>(2)</sup>
<sup>(1)</sup> No 2 RV; 50 RPM		
<sup>(2)</sup> No 6 RV; 20 RPM		

## Film properties

Method of analysis	MU	Standard
11. Peel Adhesion on Steel	g/in	1,400
17. Rolling Ball Tack	cm	2
22. Static Shear	h	4

Average values; 22±2 g/m<sup>2</sup> of dry adhesive on PET film 36 µm