

## Tackwhite A 65

### Description

TACKWHITE A 65 is a water based acrylic pressure sensitive adhesive. The dried film has a very aggressive initial tack and a good cohesion.

### Application

TACKWHITE A 65 is suitable for the production of pressure sensitive packaging and office tapes on BOPP films. By applying approximately 20-21 g/sqm dry weight, it yields a good balance of peel and shear strength. It is supplied as a ready-to-use emulsion and it is suitable for most of today's modern coating machines.

Other prerogatives:

- Very aggressive initial tack
- Good adhesion
- Good properties coating low grammage

### Packaging

The product is supplied in iron drums (200 kg); IBC containers (1000 kg).

### Storing

For a safe storage of this emulsion, keep containers well sealed to prevent water evaporation and skin formation. The emulsion must be stored between 5-25°C. Freezing must be avoided.

Use within 6 months from production date (unopened and in the original packaging).

## Technical Specifications

Method of analysis	MU	Standard
1. Total Solids	%	51±1
3. Brookfield Viscosity 25°C	mPa.s	< 400 <sup>(1)</sup>
8. pH Solvents	pH	8.5 - 9.5 water

<sup>(1)</sup> No 1 RV; 20 RPM

## Film properties

Method of analysis	MU	Standard
11. Peel Adhesion on Steel	g/in	900
22. Static Shear	h	> 200
97. Loop Tack Test	g	1,100

*Average values; 22±2 g/m<sup>2</sup> of dry adhesive on PET film 36 µm*