



Tackifier 95

OBSOLETE

Description

TACKIFIER 95 is a solvent-free, water borne tackifier dispersion. The resin component is a high grade stabilized rosin ester, designed to provide very good adhesive performance to a wide range of substrates.

Softening point of the base resin = 80°C approx.

Application

TACKIFIER 95 is mainly intended to enhance the pressure sensitive adhesive properties of polymeric latices, such as acrylates or SBR used in the field of self adhesive tapes and labels.

TACKIFIER 95 gives to the PSA a good general adhesive characteristic bound and very high shear adhesion.

TACKIFIER 95 is a fine particle size dispersion with excellent mechanical stability for high speed coating, providing wide range of compatibility in both synthetic and natural polymer latices, and improving adhesion to difficult and low surface tension films.

Packaging

The product is supplied in iron drums (200 kg); IBC containers (1000 kg).

Storing

Protect from freezing: containing no freeze/thaw stabilizers, Tackifier 95 coagulates irreversibly upon freezing.

Must be stored at temperatures between +5 and +40°C .

To prevent evaporation and subsequent formation of coarse particles, keep containers or drums well sealed.

Notes

TACKIFIER 95 is in compliance with the requirements of FDA for use in food packaging and food processing operations:
CFR 21, 175.105 Adhesive.

Technical Specifications

1. Total Solids	%
TACKIFIER 95	54±3.50
3. Brookfield Viscosity	mPa.s
25°C	
TACKIFIER 95	< 1,000 ⁽¹⁾
8. pH	pH
TACKIFIER 95	7 - 8

⁽¹⁾ N. 2 RV; 20 RPM