



Tackwhite A 69

Description

TACKWHITE A 69 is a low Tg pure Acrylic polymer emulsion that forms extremely clear, elastic and tacky films. The dried film has a very aggressive initial tack and a good cohesion.

Application

TACKWHITE A 69 has a good balance of peel and shear strength and it is suggested for the production of labels, double-sided tapes,... The addition of suitable tackifiers increases the peel adhesion strength and permits the production of superpermanent labels and the coating of foams, fabrics, synthetic leathers,...

Packaging

The product is supplied in iron drums (200 kg); IBC containers (1000 kg).

Storing

To ensure safe storage of this emulsion, containers should be well sealed to prevent the water evaporation and skin forming. The emulsion must be stored between 5-40°C. Protect from freeze.

Use within 6 months from production date (unopened and in the original packaging).

Technical Specifications

Method of analysis	MU	Standard
1. Total Solids	%	52±2
3. Brookfield Viscosity 25°C	mPa.s	200 - 600 ⁽¹⁾
8. pH Solvents	pH	8 - 9 water

⁽¹⁾ No 2 RV; 50 RPM

Film properties

Method of analysis	MU	Standard
11. Peel Adhesion on Steel	g/in	800
22. Static Shear	h	25
97. Loop Tack Test	g	1,000

Average values; 22±2 g/m² of dry adhesive on PET film 36 µm