

## Tackwhite A 33

### Description

TACKWHITE A 33 is a pure, water borne acrylic p.s.a. It is a permanent adhesive, suitable for transparent labels, tapes and any pressure sensitive article where a good resistance to the exposure to light is required.

### Application

TACKWHITE A 33 is used mainly for permanent label production (paper and film) or foams.

### Technical Specifications

Method of analysis	MU	Standard
1. Total Solids	%	51±2
8. pH	pH	8 - 10
Solvents		water
3. Brookfield Viscosity 25°C	mPa.s	
TACKWHITE A 33		200 - 500 <sup>(1)</sup>
TACKWHITE A 33 (V1)		12,000 - 22,000 <sup>(2)</sup>

<sup>(1)</sup> No 1 RV; 20 RPM  
<sup>(2)</sup> N. 5 RV; 20 RPM

### Handling

The product can be applied by traditional coating method: Mayer bar, reverse roll,... Coating weight depends on the final application, usually it is between 15 and 25 g/sqm dry.

### Packaging

The product is supplied in iron drums (200 kg); IBC containers (1000 kg).

### Storing

TACKWHITE A 33 must be stored at temperatures between +5°C and +40°C.

Use within 6 months from production date (unopened and in the original packaging).

### Film properties

Method of analysis	MU	Standard
11. Peel Adhesion on Steel	g/in	1,200
22. Static Shear	h	> 50
97. Loop Tack Test	g	800

*Average values; 22±2 g/m<sup>2</sup> of dry adhesive on PET film 36 µm*