



Tackifier 15

OBSOLETE

Description

TACKIFIER 15 is a solvent-free, water borne tackifier dispersion of a mixed aliphatic-aromatic hydrocarbon resin, designed to provide very good adhesive performance to a wide range of substrates.

Ring & Ball value of the base resin = 85°C approx.

Application

TACKIFIER 15 is primarily intended to enhance the pressure sensitive adhesive properties of polymeric latices, such as acrylates or SBR used in the field of self adhesive tapes and labels.

TACKIFIER 15 imparts to the PSA a high adhesion. TACKIFIER 15 is a fine particle size dispersion with excellent mechanical stability for high speed coating, ensuring a wide range of compatibility in both synthetic and natural polymer latices, and improving adhesion to difficult and low surface energy films.

Storing

Protect from freezing: containing no freeze/thaw stabilizers, TACKIFIER 15 coagulates irreversibly upon freezing.

Must be stored at temperature between +5 and +40°C .

To prevent evaporation and subsequent formation of coarse particles, keep containers or drums well sealed.

Technical Specifications

1. Total Solids	%
TACKIFIER 15	51±1.50
3. Brookfield Viscosity 25°C	mPa.s
TACKIFIER 15	50 - 1,000 ⁽¹⁾
8. pH	pH
TACKIFIER 15	7 - 8

⁽¹⁾ N. 2 RV; 20 RPM

Packaging

The product is supplied in iron drums (200 kg); IBC containers (1000 kg).