# Thickener SL 6103

## Description

Thickener SL 6103 is a very stable waterborne emulsion of a light molecular weight acrylic polymer.
Appearance: milky white liquid.

## Application

It is used as a thickening agent in waterborne emulsion of natural and/or synthetic latex. It can be used at concentrations up to 6% and it has to be neutralized. It can increase the viscosity of the emulsion to the desired level.
Note: viscosity increases with the pH reaching its maximum when the acid is completely neutralized. Viscosity increases in 24-48 hours, depending also upon temperature.

## Technical Specifications

| Method of analysis | MU | Standard |
|---|---|---|
| 1. Total Solids | % | 28±0.50 |
| 8. pH | | 2.1 - 3.5 |
| 15. Appearance | | white milky liquid |
| Solvents | | water |

## Packaging

The product is supplied in plastic tanks (10 kg); plastic drums (50 kg); iron drums (200 kg); IBC containers (1000 kg).

## Storing

Thickener SL 6013 must be stored at temperatures between +5°C and +40°C.

Use within 12 months from production date (unopened and in the original packaging).

Build date 11 Sep 2025



*Above information is reliable, but does not constitute warranty.*

**ICHEMCO srl**
via 11 Settembre, 5 - 20012 CUGGIONO (MI) - ITALY
Phone: +39 02 97243.1 - info@ichemco.it - www.ichemco.it