



Tacksol 10/89 SCB UV Plus

(Provisional)

Description

TACKSOL 10/89 SCB UV PLUS is a pressure sensitive adhesive, based on natural rubber and special resins dissolved in hydrocarbons C6-C7 (benzine). It contains special additives to guarantee a long term UV protection. After curing, it develops a very good resistance to ageing and heat.

Application

TACKSOL 10/89 SCB UV PLUS can be applied on any substrate (paper, PET, PP, PE, PVC,...). When TACKSOL 10/89 SCB UV PLUS is applied on PVC, a suitable primer is needed, whereas it can be applied directly on other substrates. This product is recommended for the production of protective films and tapes for rough surfaces.

Storing

Store at temperature not higher than + 40°C, protected from heat sources and direct sunlight. Keep containers well closed, to prevent solvent evaporation. In case of prolonged storage, stir well before use.

Use within 12 months from production date (unopened and in the original packaging).

Technical Specifications

Method of analysis	MU	Standard
1. Total Solids	%	25±1

Handling

For protective tapes, the product must be cured with isocyanate (e.g. CURING AGENT RF/AEDE); in this case the pot-life of the adhesive is reduced as crosslinking starts immediately after the addition of the curing agent. The amount of isocyanate depends on the final properties requested.

Packaging

The product is supplied in iron drums (145 kg); ADR compliant IBC containers (750 kg).

Build date 18 Sep 2024