ichemco
Developing Chemical Excellence

member of Afera

CERTIFIED MANAGEMENT SYSTEMS
CERTIQUALITY
UNI EN ISO **9001:2015**
UNI EN ISO **14001:2015**
UNI ISO **45001:2018**

Tackifier 95 B

(Provisional)

Description

TACKIFIER 95 B is an APEO-free, water borne tackifier dispersion. The resin component is a high grade stabilized rosin ester, designed to provide very good adhesive performance to a wide range of substrates.

Application

TACKIFIER 95 B is mainly intended to enhance the pressure sensitive adhesive properties of polymeric latices, such as acrylates or SBR used in the field of self adhesive tapes and labels.
TACKIFIER 95 B gives very high peel adhesion and tack to the PSA, it increases the adhesion on difficult and low tension surfaces.
TACKIFIER 95 B is a fine particle size dispersion with excellent mechanical stability for high speed coating, providing wide range of compatibility in both synthetic and natural polymer latices, and improving adhesion to difficult and low surface tension films.

Technical Specifications

Method of analysis	UoM	Standard
1. Total Solids	%	54 ± 2
3. Brookfield Viscosity 25°C	mPa.s	≤ 1500 (1)
4. Softening Point, Ring & Ball	°C	80
8. pH		6.5 ÷ 8

(1) N. 2 RV; 20 RPM

Solvents: water

Packaging

The product is supplied in iron drums (200 kg); IBC containers (1000 kg).

Storing

Protect from freezing: containing no freeze/thaw stabilizers, Tackifier 95 coagulates irreversibly upon freezing.
Must be stored at temperatures between +5 and +40°C .
To prevent evaporation and subsequent formation of coarse particles, keep containers or drums well sealed.

Stir well before use.

Use within 6 months from production date (unopened and in the original packaging).

Above information is reliable, but does not constitute warranty.

ICHEMCO srl
via 11 Settembre, 15 - 20012 CUGGIONO (MI) - ITALY
Phone: +39 02 97243.1 - info@ichemco.it - www.ichemco.it