



# Release PP 25 Eco Dil. 0,5

## Description

**RELEASE PP 25 ECO DIL. 0,5** is a polyvinylcarbamate in solvent solution. It does not contain aromatic solvents.

## Application

The product is a very efficient release agent for polypropylene, polyethylene, PVC, reinforced PVC and polyester films with natural, synthetic rubber and acrylic adhesives. It also designed to be used with the three steps printing process of PSA tapes, when aromatic solvents are not accepted.

## Technical Specifications

Method of analysis	UoM	Standard
1. Total Solids	%	0.5 ± 0.05
Solvents	octane / isopropyl alcohol	

## Handling

Apply 3-5 g/sqm of **RELEASE PP 25 ECO DIL. 0,5** as the final overcoat after printing. Drying must be very efficient, in order to avoid any solvent residue, which could cause ink transfer to the adhesive side.

The presence of a small amount of ink into the release bath is to be considered acceptable and does not affect the quality of printing.

## Packaging

The product is supplied in Iron drums (18 kg); ADR compliant IBC containers (700 kg).

## Storing

Product must be stored at temperatures higher than +18°C, far from direct sunlight.

Use within 12 months from production date (unopened and in the original packaging).

## Notes

**RELEASE PP 25 ECO DIL. 0,5** tends to jellify at temperatures lower than +20°C: the solution becomes hazy and some material settles down to the bottom of the container. It is necessary to restore the original conditions before use, it is sufficient to heat the product at 35-40°C and stir to complete homogeneity.