



# Tackwhite A 38

## Description

TACKWHITE A38 is an acrylic dispersion used for wash-removable labels.

## Application

Water borne pressure sensitive adhesive used for wash removable labels.

The product has a good removability in alkaline water: at 70°C clean removal in 15-30 sec.

## Technical Specifications

Method of analysis	MU	Standard
1. Total Solids	%	48±1
3. Brookfield Viscosity 25°C	mPa.s	100 - 500 <sup>(1)</sup>
8. pH Solvents	pH	8 - 9 water

<sup>(1)</sup> No 1 RV; 20 RPM

## Film properties

Method of analysis	MU	Standard
11. Peel Adhesion on Steel	g/in	1,100
17. Rolling Ball Tack	cm	10
22. Static Shear	h	> 2
97. Loop Tack Test	g	1,500

*Average values; 22±2 g/m<sup>2</sup> of dry adhesive on PET film 36 µm*

## Handling

The product can be applied using traditional coating systems: Mayer bar, reverse gravure,...

The product can be thickened using polyurethanic or acrylic thickeners (e.g. THICKENER SL 6103).

## Packaging

The product is supplied in iron drums (200 kg); IBC containers (1000 kg).

## Storing

Protect from freezing.

Keep at temperatures between +5 and +35°C.

Use within 6 months from production date (unopened and in the original packaging).