



Tackifier 66

OBSOLETE

Description

TACKIFIER 66 is a solvent-free, water borne tackifier dispersion. The resin component is a high grade stabilized rosin ester, designed to provide very good adhesive performance to a wide range of substrates.

Application

TACKIFIER 66 is primarily intended to enhance the pressure sensitive adhesive properties of polymeric latices, such as acrylates or SBR used in the field of self adhesive tapes and labels.

TACKIFIER 66 imparts to the PSA a good general adhesive characteristic bound to very high shear adhesion.

TACKIFIER 66 is a fine particle size dispersion with excellent mechanical stability for high speed coating, providing wide range of compatibility in both synthetic and natural polymer latices, and improving adhesion to difficult and low surfaces.

Packaging

200 l drums or 1000 l plastic tanks.

Storing

Protect from freezing: containing no freeze/thaw stabilizers, Tackifier 66 coagulates irreversibly upon freezing.

Must be stored at temperature between +5 and +40°C .

To prevent evaporation and subsequent formation of coarse particles, keep containers or drums closed.

Shelf-life is 3 months.

Notes

TACKIFIER 66 is in compliance with the requirements of FDA for use in food packaging and food processing operations:
CFR 21, 175.105 Adhesive.

Technical Specifications

1. Total Solids	%
TACKIFIER 66	50±2
3. Brookfield Viscosity 25°C	mPa.s
TACKIFIER 66	200 - 400 ⁽¹⁾
4. Softening Point, Ring & Ball	°C
TACKIFIER 66	61
8. pH	pH
TACKIFIER 66	6 - 8

⁽¹⁾ N. 2 RV; 20 RPM