ichemco
Developing Chemical Excellence

CERTIFIED MANAGEMENT SYSTEMS
CERTIQUALITY
UNI EN ISO 9001:2015
UNI EN ISO 14001:2015
UNI ISO 45001:2018

Tackwhite A 33

Description

TACKWHITE A 33 is a pure, water borne acrylic p.s.a. It is a permanent adhesive, suitable for transparent labels, tapes and any pressure sensitive article where a good resistance to the exposure to light is required.

Application

TACKWHITE A 33 is used mainly for permanent label production (paper and film) or foams.

Technical Specifications

Method of analysis	MU	Standard
1. Total Solids	%	51±2
8. pH		8 - 10
Solvents		water
3. Brookfield Viscosity 25°C	mPa.s	
TACKWHITE A 33		200 - 500 (1)
TACKWHITE A 33 (V1)		12000 - 22000 (2)

(1) No 1 RV; 20 RPM
(2) N. 5 RV; 20 RPM

Film properties

Method of analysis	MU	Standard
11. Peel Adhesion on Steel	g/in	1,200
22. Static Shear	h	> 50
97. Loop Tack Test	g	800

Average values; 22±2 g/m² of dry adhesive on PET film 36 µm

Handling

The product can be applied by traditional coating method: Mayer bar, reverse roll,... Coating weight depends on the final application, usually it is between 15 and 25 g/sqm dry.

Packaging

The product is supplied in iron drums (200 kg); IBC containers (1000 kg).

Storing

TACKWHITE A 33 must be stored at temperatures between +5°C and +40°C.

Use within 6 months from production date (unopened and in the original packaging).

Build date 11 Sep 2025

Above information is reliable, but does not constitute warranty.

ICHEMCO srl
via 11 Settembre, 5 - 20012 CUGGIONO (MI) - ITALY
Phone: +39 02 97243.1 - info@ichemco.it - www.ichemco.it