



# Tackwhite A 22 RP

## Description

TACKWHITE A 22 RP is a waterborne pressure sensitive adhesive, based on acrylic polymers. The coated product has a very high resistance to plasticizers and humidity. It can be classified as a permanent adhesive.

## Application

TACKWHITE A 22 RP is designed for the production of labels in plastic film (especially PPVC).

## Technical Specifications

Method of analysis	MU	Standard
1. Total Solids	%	51±1
3. Brookfield Viscosity 25°C	mPa.s	10 - 250 <sup>(1)</sup>
8. pH Solvents	pH	5 - 7 water

<sup>(1)</sup> No 1 RV; 20 RPM

## Film properties

Method of analysis	MU	Standard
11. Peel Adhesion on Steel	g/in	1,300
17. Rolling Ball Tack	cm	10
22. Static Shear	h	> 100
97. Loop Tack Test	g	1,200

*Average values; 22±2 g/m<sup>2</sup> of dry adhesive on PET film 36 µm*

## Handling

The product can be applied by Mayer bar or reverse roll.

If necessary, it can be thickened with a suitable acrylic based thickener.

## Packaging

The product is supplied in iron drums (200 kg); IBC containers (1000 kg).

## Storing

TACKWHITE A 22 RP must be stored at temperature between +5°C and +40°C. Protect from freeze.

Use within 6 months from production date (unopened and in the original packaging).